

EUROFLEX CE LED Backlit
(570gr, 1100/1100d)

Product code : CE – LED - xxx

EUROFLEX CE LED is treated on both sides with special coating for outdoor Backlit Signage. Special front coating recipe is designed for self-adhesive film application.

- Approx. 570gr/m² +/- 3%
- Is anti wicking
- Is UV stabilized
- IS anti fungal and anti mildew resistant
- Is cadmium free
- Is produced as per European Sign Industry requirement

Base Fabric	(DIN 60001)	Polyester
Yarn W/F	(DIN 53830)	1100/1100 dtex
Thickness	(DIN 53830)	0,50 mm
Density (W/F per cm)		7/7 count/cm
Total Weight	(DIN 53352)	570 grs/m²
Tensile Strength	(DIN 53354)	1400/1225 N/5cm
Tear Strength	(DIN 53363)	175/110N
Elongation	(DIN 53354)	22/25 %
Adhesion Strength	(DIN 53357)	175 N/5cm
Maximum Width	(DIN 53851)	500 cm
Flame Retardant		Self Extinguishing
Light transmission		45%
Recomended Cleaning Period	Normal	6 Months
	City Center	3 Months
UV Resistance	Zone 1	5 Years
	Zone 2	4 Years
	Zone 3	3 Years

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall WERBE-Service Burmeister be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet. All vinyls are sold subject to our Conditions of Sales. WERBE-Service Burmeister also retains the right to change sizes and specification of products without prior notice.

Zones

Zones Zone 1	Austria, Benelux, North France, Germany, North Italy, Scandinavia, Switzerland, Canada, UK, Spain, R, Portugal, Slovak republic, Czech republic, Poland, Hungary, Slovenia
Zone 2	South France, South Italy, Greece, Turkey, Portugal, Spain, Mediterranean Islands, USA, South America, North Asia, Croatia
Zone 3	South Asia, Carribean Islands, Mexico, M. East, Australia, North Africa, South Africa, Latin America, USA (AE, NV, NW, TX, CA, FL), China, India, Pakistan