

**EUROFLEX CE 23oz 18/12 FR**  
**( 780gr, 500x100d )**

**Product code : CE – xxx**

**EUROFLEX CE** is treated on both sides with special coating for outdoor Backlit Signage. Special front coating recipe is designed for self-adhesive film application.

- Approx. 780 gr/m<sup>2</sup> +/- 3%
- Is anti wicking
- Is UV stabilized
- IS anti fungal and anti mildew resistant
- Is cadmium free
- Is produced as per European Sign Industry requirement
- Has pattern weave polyester scrim
- Decoration Method :
  - Self-Adhesive Film
  - Silk Screen, airbrush by hand gun

<b>Product code</b>	<b>Metric</b>
<b>CE – 102</b>	<b>1,02 x 50 m</b>
<b>CE – 112</b>	<b>1,12 x 50 m</b>
<b>CE – 122</b>	<b>1,22 x 50 m</b>
<b>CE – 135</b>	<b>1,35 x 50 m</b>
<b>CE – 152</b>	<b>1,52 x 50 m</b>
<b>CE – 165*</b>	<b>1,65 x 50 m</b>
<b>CE – 184</b>	<b>1,84 x 50 m</b>
<b>CE – 205*</b>	<b>2,05 x 50 m</b>
<b>CE – 225</b>	<b>2,25 x 50 m</b>
<b>CE – 320</b>	<b>3,20 x 50 m</b>
<b>CE – 420</b>	<b>4,20 x 50 m</b>
<b>CE – 500*</b>	<b>5,00 x 50 m</b>

\* Custom size – please call for availability.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall WERBE-Service be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet. WERBE-Service also retains the right to change sizes and specification of products without prior notice.

<b>Description</b>		<b>Unique flexible reinforced PVC vinyl for Backlit signs and awnings. Both sides are lacquered with our specialised CE coating.</b>
<b>Weight</b>		<b>780 gr/m<sup>2</sup> +/- 3%</b>
<b>Base Cloth</b>		<b>High Tensile polyester 500x1000 Denier</b>
<b>Weave</b>		<b>14 x 10 per 2 cm</b>
<b>Thickness</b>		<b>0,6 mm</b>
<b>Tensile Strength</b>		<b>165/165 kg/5cm</b>
<b>Elongation</b>		<b>25/35%</b>
<b>Tear</b>		<b>25/34kg</b>
<b>Cold Crack</b>		<b>- 30°C</b>
<b>Heat Resistance</b>		<b>+ 70°C</b>
<b>Flame – retardant</b>		<b>Self – Extinguishing</b>
<b>Anti Wicking</b>		<b>Treated</b>
<b>Anti Mildew</b>		<b>Treated</b>
<b>Ultra Violet</b>		<b>Protected</b>
<b>UV Resistance</b>	<b>Zone 1</b>	<b>7 years</b>
	<b>Zone 2</b>	<b>5 years</b>
	<b>Zone 3</b>	<b>4 years</b>
<b>Max Width</b>		<b>500</b>

## Zones

<b>Zone 1</b>	Austria, Benelux, North France, Germany, North Italy, Scandinavia, Switzerland, Canada, UK, Spain, R, Portugal, Slovak republic, Czech republic, Poland, Hungary, Slovenia
<b>Zone 2</b>	South France, South Italy, Greece, Turkey, Portugal, Spain, Mediterranean Islands, USA, South America, North Asia, Croatia
<b>Zone 3</b>	South Asia, Carribean Islands, Mexico, M. East, Australia, North Africa, South Africa, Latin America, USA (AE, NV, NW, TX, CA, FL), China, India, Pakistan

## Warranty Zoning

The warranty issued in support of each WERBE-Service product our confidence in the performance of the material under normal conditions. The performance of all products will of course by extrens of climate and air pollution. To accommodate these worldwide fluctuations you will find our specification sheet for individual product contains a Zone reference. WERBE-Service retains the right to change sizes and specifications without pror notice – all our products are sold subject to our conditions of Sales and Customer Notice.